

FAX MESSAGE

FROM : APF PAC KAMRA
FAX NO.051-9225514

TO : PUBLIC PROCUREMENT
REGULATORY AUTHORITY
FAX NO. 051-9219149

REF : APF/1920/42/LOG/PC-30 DATED NOVEMBER , 2017

UPLOADING OF TENDER ON PPRA WEB SITE

KINDLY UPLOAD THE UNDERMENTIONED TENDER NOTICE ON PPRA WEBSITE AND FORWARD BILL ALONGWITH TS NO FOR OUR FURTHER NECESSARY ACTION.

OPEN TENDER NOTICE

1. TECHNICAL AND COMMERCIAL OFFERS FOR PROCUREMENT OF UNDERMENTIONED ITEM MAY BE SUBMITTED IN **SEPARATE SEALED ENVELOPES** TO THE FOLLOWING FACTORY ADDRESS.

AVIONICS PRODUCTION FACTORY PAC BOARD KAMRA DISTT ATTOCK

PART NO	NOUN	QTY	UI	SPECIFICATION
6730PK0002230	MULTIMEDIA PROJECTOR	01	EA	ATTACHED

TERMS AND CONDITIONS:-

2. GENERAL TERMS AND CONDITIONS ARE MENTIONED IN TENDER FORM (APF/ LG-7). TENDER FORM AND COMPLETE DETAILS / SPECIFICATIONS OF ITEM, IF REQUIRED CAN BE OBTAINED FROM CONTACT NO **051-9099-6813,6468** ON ANY WORKING DAY BEFORE OPENING OF TENDER.

3. THE FIRM MUST BE GST AND PROFESSIONAL TAX REGISTERED HAVING NTN. **INTERESTED FIRMS ARE TO DEPOSIT 5% BID SECURITY ALONG WITH QUOTATION.**

4. TECHNICAL AND COMMERCIAL OFFERS OF ABOVE MENTIONED ITEM MAY BE SUBMITTED IN SEALED ENVELOPES IN **TENDER BOX NO. 01** PLACED AT MAIN GUARD ROOM APF.

FAX MESSAGE

5. LAST DATE FOR SUBMISSION OF TENDERS IS **05 DECEMBER, 2017** BEFORE **1100 HRS**.
6. THE TENDERS WILL BE OPENED ON THE SAME DAY AT **1130 HRS** IN THE OFFICE OF DIRECTOR LOGISTICS (S&A), APF, PAC, KAMRA.
7. PAYMENT WILL BE SUBJECT TO THE ACCEPTANCE OF ITEM BY THE USER AND QUALITY DIRECTORATE.
8. FIRMS HAVING THE CAPABILITY TO PROVIDE ABOVE MENTIONED ITEM AS PER GIVEN SPECIFICATIONS ARE TO QUOTE.
9. INTERESTED FIRMS ARE TO PROVIDE SAMPLES / TECHNICAL DATA ALONG WITH TECHNICAL QUOTATIONS.
10. ONLY REGISTERED SUPPLIERS, WHO ARE ON ACTIVE TAXPAYERS LIST ARE TO PROVIDE DOCUMENTARY PROOF AND QUOTE ABOVE MENTIONED ITEMS.
11. THIS FACTORY RESERVES THE RIGHT TO REJECT ANY QUOTATION ON TECHNICAL GROUNDS.
12. QUOTATION MUST BE VALID FOR MINIMUM **90 DAYS**.
13. SALES TAX AS APPLICABLE MUST BE MENTIONED SEPARATELY.
14. GUARANTEE/ WARRANTY TERMS AND DELIVERY PERIOD SHOULD BE MENTIONED SEPERATELY.

(TILAL MAZHAR)
FLIGHT LIEUTENANT
FOR MANAGING DIRECTOR
APF PAC KAMRA
TEL EXT: 051-9099-
6292

FAX MESSAGE**SPECIFICATION OF MULTIMEDIA PROJECTOR**

OPTICAL	
DISPLAY SYSTEM	3 LCD SYSTEM
LIGHT SOURCE	ULTRA HIGH-PRESSURE MERCURY LAMP 210W TYPE
LIGHT OUTPUT (HIGH/STANDARD/LOW)	3700 LM / 2700 LM / 2100 LM
COLOR LIGHT OUTPUT (HIGH/STANDARD/LOW)	3700 LM / 2700 LM / 2100 LM
SCREEN SIZE (MEASURED DIAGONALLY)	30" TO 300"
LCD PANEL TYPE	0.63" X 3 BRIGHTERA
NUMBER OF PIXELS	2,359,296 (1024 X 768 X 3) PIXELS
NATIVE RESOLUTION	XGA
ASPECT RATIO	4:03
THROW RATIO	.1.40 : 1 TO 2.27 : 1
THROW DISTANCE	PLEASE REFER TO OUR PROJECTOR THROW DISTANCE CALCULATOR - DATA PROJECTOR SIMULATOR
KEystone CORRECTION (VERTICAL / HORIZONTAL)	±30° / -
PROJECTION LENS	
LENS ZOOM	MANUAL APPROX. 1.6X
LENS FOCUS	MANUAL
SIGNALS	
CONTRAST RATIO	3,000:1
RESOLUTION	PANEL DISPLAY: 1024X768 DOTS
COLOUR SYSTEM	NTSC3.58, PAL, SECAM, NTSC4.43, PAL-M, PAL-N
DISPLAY RESOLUTION : VIDEO SIGNAL INPUT	NTSC, PAL, SECAM, 480/60I, 576/50I, 480/60P, 576/50P, 720/60P, 720/50P, 1080/60I, 1080/50I, 1080/60P, 1080/50P
DISPLAY RESOLUTION : COMPUTER SIGNAL INPUT	MAXIMUM DISPLAY (RESIZING): UXGA 1600X1200 DOTS
DISPLAYABLE SCANNING FREQUENCY	FH: 14 KHZ TO 93 KHZ, FV: 47 HZ TO 93HZ
GENERAL	
DIMENSION (WXHxD) (WITHOUT PROTRUSION)	365 X 96.2 X 252 MM
MASS	APPROX. 3.8 KG (8 LB 6 OZ)
POWER REQUIREMENT	AC 100V TO 240V, 2.8A TO 1.2A, 50/60 HZ
OPERATING TEMPERATURE	0°C TO 40°C
OPERATING HUMIDITY	35% TO 85% (NO CONDENSATION)
STORAGE TEMPERATURE	(-20°C TO +60°C)
STORAGE HUMIDITY	10% TO 90%

FAX MESSAGE

POWER CONSUMPTION MAX (AC220V TO 240V, AC100V TO 120V)	268W/218W/189W, 276W/225W/196W (LAMP MODE : HIGH/STANDARD/LOW)*
POWER CONSUMPTION STANDBY (AC220V TO 240V, AC100V TO 120V)	5.9W / 0.5W
HEAT DISSIPATION (AC220V TO 240V, AC100V TO 120V)	915 BTU, 942 BTU
INPUT INTERFACE	
INPUT A	RGB /Y PB PR INPUT CONNECTOR : MINI D-SUB 15-PIN (FEMALE)
INPUT B	RGB INPUT CONNECTOR : MINI D-SUB 15-PIN (FEMALE)
INPUT C	HDMI INPUT CONNECTOR : HDMI 19-PIN, HDCP SUPPORT
S VIDEO IN	S VIDEO INPUT CONNECTOR : MINI DIN 4-PIN
VIDEO IN	VIDEO INPUT CONNECTOR : PIN JACK
OUTPUT	MONITOR OUTPUT CONNECTOR : MINI D-SUB 15-PIN (FEMALE)
CONTROL SIGNAL INPUT/OUTPUT	RS-232C CONNECTOR : D-SUB 9-PIN (MALE), LAN CONNECTOR : RJ-45, 10BASE-T/100BASE-TX, USB : TYPE A, TYPE B

SCREEN

SCREEN	8X12 FEET
--------	-----------